



Note:  
The AKZ(H) in the name means: A(H) and Z(H).

6	Pin	Copper alloy	Sn Plated
5	Slider	Stainless steel	/
4	Spring	Stainless steel	/
3	Lever	PA66+GF	UL94V-0
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0



MATERIAL:	SURFACE/COLOR:
MAT. NO./REV.:	MAT STATUS: 批量

APPR:	宋伟明	2022.12.27	NAME	DC2206V-7.5-XXP-1Y-00AKZ(H)
CHKD:	张玉华	2022.12.23	MAT. NO./REV.:	/ 00
DRAFT:	阮坤坤	2022.12.22	DRAWING NO.	200123509
DRAFT:	阮坤坤	2022.12.22	TYPE	CUSTOMER DRAWING
DRAFT:	A4	(THRU)	DRAWING STATUS	已发布
SCALE	1.5:1	SHEET	1/1	

公差/General tolerances(mm)		0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±2°
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50		

N=01P			
UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	600/41	600/41	/
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	800/41	1000/41	1000/41
额定脉冲电压(kV)/Rate Impulse Voltage(kV)	8	8	8
N=02-12P			
UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/41	150/41	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	500/41	690/41	1000/41
额定脉冲电压(kV)/Rate Impulse Voltage(kV)	6	6	6
线径范围(硬线和软线)/Wire Range(rigid and flexib) (AWG/mm <sup>2</sup> )	24~8 / 0.2~6.10(sol)		
剥线长度/Stripping length(mm)	11~13		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		