



公差/General Tolerances(mm)		公差/General Tolerances(mm)	
0	>3	>6	>18
~	~	~	~
3	6	10	18
~	~	~	~
±0.12	±0.18	±0.22	±0.26
±0.31	±0.37	±0.57	±0.80
±1.05	±1.15	±1.60	±2.20
±2.50	±2.50	±2.50	±2.50
0.1/10	~	~	~
±Z	±Z	±Z	±Z



ITEM	NAME OF PART	MATERIAL	NOTES
3	Screw	Steel	Ni Plated
2	Pin Header	Brass	Sn Plated
1	Housing	P66	UL94V-0

UL 标准/UL Standard:		B	C	D
额定电压/Rated Voltage(V)	Current(A)	300/20	300/20	300/10
IEC 标准/IEC Standard:				
过压类别/Overvoltage Category/污染等级		III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)		500/32	600/32	1000/32
额定脉冲电压/电流/Rate Impulse Voltage(KV)		6	6	6
额定扭矩/Torque Tightening(N·m/Lb·in)		M4, 1.2/10.63		
绞线范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)		0.34~4/22~12		
间距/Pitch(mm)	绞线范围/Poles	10.00/N=02~26P		
剥线长度/Stripping length(mm)		/		
使用温度范围/Operating temperature(°C)		-40~+105		
符合RoHS环保要求/Conform to RoHS		Yes		

SURFACE: /

MATERIAL: /
 MAT NO.: /
 STATUS: /
 APPD: /
 CHKD: /

NAME: **DEGSON** 宁波高松电子有限公司
 NINGBO DEGSON ELECTRICAL CO., LTD

DRAWING NO.: DG55H-E01
 TYPE: CUSTOMER DRAWING
 SCALE: 1:1
 SHEET 1/1

REV	ECN	DESCRIPTION	DRAFT	DATE